

February, 2011

3M™ Vinyl Tape 471

Product Description

3M™ Vinyl Tape 471 is a conformable colored (9 colors plus transparent) tape made from vinyl backing with rubber adhesive. It is ideal for many lane and safety markings, color coding, abrasion protection, masking, sealing, splicing and other general purpose applications.

Product Features

- Pigmented backings maintain their vivid colors even when exposed to heavy abrasion.
- Can be sold to Commercial Item Description A-A-1689 Type I & II
- Conformability and dead stretch properties are ideal for taping, wrapping or sealing many curved, convex, or irregular surfaces.
- Rubber adhesive provides good adhesion to many surfaces for easier application and excellent holding strength.
- Sharp colors for color coding or marking systems, draw attention and help enhance plant safety.
- Clean removal from many surfaces which helps reduce clean-up and labor costs.
- Abrasion resistant and longer potential application life.
- Good solvent resistance for application protection and longer product life.



3M™ Vinyl Tape 471

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

| Property | Values | | Method |
|----------------------------------|---|---------|-------------------|
| Color | Yellow, white, red, black, brown, green, orange, purple, blue | | |
| Total Tape Thickness | 0.14 mm | 5.2 mil | ASTM D3652 |
| Backing Thickness | 0.1 mm | 4.1 mil | ASTM D3652 |
| Adhesive | Rubber | | |
| Low Leachable Halogen and Sulfur | Passes | | MIL-STD-2041D(SH) |

Typical Performance Characteristics

| Property | Values | | Method | Substrate |
|-----------------------|------------|--------------|------------|-----------------|
| Peel Adhesion | 2.5 N/cm | 23 oz/in | ASTM D3330 | Stainless Steel |
| Tensile Strength | 24.5 N/cm | 224 oz/in | ASTM D3759 | |
| Elongation at Break | 130 % | | ASTM D3759 | |
| Temperature Use Range | 4 to 77 °C | 40 to 170 °F | | |

Available Sizes

| Property | Values | |
|----------------------|--------|-------|
| Standard Roll Length | 33 m | 36 yd |

Handling/Application Information

Application Ideas

- Excellent for many lane and safety marking applications. When used with an applicator like the M-77 dispenser, 3M™ Vinyl Tape 471 can be quickly applied to define storage and safety areas. The fact that 3M tape 471 tape is quickly and cleanly removed in most cases makes it a faster, more versatile and less costly option than painting. Using tape for lane marking instead of painting also eliminates the need to ventilate paint solvents from an open area.
- Because it has low leachable halogens and sulfur, 3M™ Vinyl Tapes 471 can be used in corrosion sensitive applications like the nuclear and stainless steel industries.
- 3M tape 471 stretches to seal canisters and other storage containers that require a tight seal.
- Vivid colors of the tapes make them ideal for color, coding and decorating.

Handling/Application Information (continued)

Application Techniques

• Best results are attained when applied to a clean, dry surface at temperatures between 60° to 85°F (16° to 27°C).
 Note: While 3M tape 471 resists many common solvents, it should not be exposed to ketones, chlorinated hydrocarbons and esters found in lacquer thinner, degreasers, paint strippers, etc., which may cause the backing to swell or curl.

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.
 To obtain best performance, use this product within 18 months from date of manufacture.

Industry Specifications

Can be sold to Commercial Item Description A-A-1689 Type I & II

Trademarks

3M is a trademark of 3M Company.

References

Safety Data Sheet (SDS)

https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=471

Family Group

| | 471 | 4712 (Linered) | 471 (Transparent) | 4712 (Linered, Transparent) |
|---------------------------|---|---|-------------------|-----------------------------|
| Color | Yellow, white, red, black, brown, green, orange, purple, blue | Yellow, white, red, black, brown, green, orange, purple, blue | Transparent | Transparent |
| Total Tape Thickness (mm) | 0.14 | 0.14 | 0.14 | 0.14 |
| Backing Thickness (mm) | 0.1 | 0.1 | 0.1 | 0.1 |
| Adhesive | Rubber | Rubber | Rubber | Rubber |
| Tensile Strength (N/cm) | 24.5 | 24.5 | 24.5 | 24.5 |

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

