

August, 2013

## 3M™ Polyester Film Tape 850 Silver

### Product Description

3M™ Polyester Film Tape 850 can generally be used for splicing and applications where chemical resistance and/or clean removal is necessary. The silver backing is a transparent polyester with a thin layer of aluminum.

### Product Features

- Prolonged exposure to sunlight or hot caustics will cause backing to become brittle and lose tensile strength.
- Thin, high strength polyester film helps reduce failures due to breakage while meeting low caliper requirements.
- Chemical and solvent resistance to help reduce rejects produced from chemical and solvent attack.
- Abrasion resistant to help protect surfaces from abrasion and rough handling.
- Variety of colors offered when easy detection is required.



# 3M™ Polyester Film Tape 850 Silver

## Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## Typical Physical Properties

Property	Values		Method
Color	Silver		
Backing Thickness	0.02 mm	0.9 mil	ASTM D3652
Backing	Polyester		
Adhesive	Acrylic		
Water Vapor Transmission Rate	7.75 g/m <sup>2</sup> /24 hr	0.9 g/100 in <sup>2</sup> /24 hr	ASTM D3833

## Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	4.6 N/cm	42 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	49 N/cm	448 oz/in	ASTM D3759	
Elongation at Break	120 %		ASTM D3759	
Temperature Use Range	-50 to 150 °C	-60 to 300 °F		

## Available Sizes

Property	Values	
Standard Roll Length	65.8 m	72 yd

## Handling/Application Information

### Application Ideas

- Post splicing movie film.
- Defect flagging where reflective sensing is required.
- Decorative striping and die cutting.
- Decorative edging.

### Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% relative humidity in the original packaging material. To obtain best performance, use this product within 18 months from date of manufacture.

### Trademarks

3M is a trademark of 3M Company.

# 3M™ Polyester Film Tape 850 Silver

## References

### Safety Data Sheet (SDS)

[https://www.3m.com/3M/en\\_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en\\_US&co=ptn&q=850 Silver](https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=850 Silver)

## Family Group

	850	850 Silver
Color	Transparent, Red, Black, White	Silver
Backing Thickness (mm)	0.02	0.02
Backing	Polyester	Polyester
Adhesive	Acrylic	Acrylic
Tensile Strength (N/cm)	49	49

## ISO Statement

This product was manufactured under a quality system registered to ISO 9001 standards.

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method or application.

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

