Technical Data

Issue 10 July 2002

AT8 PVC Lane Marking Tape

General description

A heavy duty plasticised PVC film coated with a white high adhesion, high tack and aggressive pressure sensitive adhesive.

- Excellent conformability, particularly to uneven surfaces.
- Specially formulated PVC prevents lifting.
- Water resistant.
- Good abrasion resistance.
- UV resistant.
- Very aggressive adhesive.
- Can be walked on immediately after application.
- Suitable for outdoor applications.
- Suitable for machine and hand application.
- Colours and widths in accordance with the British Sports Council.

Specifications

Certification* to the following standards may be available on request. BS3887 : 1991 all colours

Technical Details

Typical values

Tape Thickness	0.14mm
Breaking Load	26 N/cm
Elongation at Break	150%
Adhesion Steel Self	3.5 N/cm 2.5 N/cm
Water Extract pH Conductivity	6.0 to 8.0 Max.2.5 mS/m
Service Temperature	$0^{\circ}C$ to $+60^{\circ}C$
Application Temp	+5°C to +40°C

*Standard charge for certificate: £25.00.

NOTE
Except where indicated otherwise, the above figures are
average values and should not be regarded as MAXIMUM
or MINIMUM values for specification purposes. The
Company reserves the right to improve products and any
change in specification will result in a re-issue of the
relevant 'Technical Data Sheet'. Customers should satisfy
themselves that the tape is suitable for their requirements
whether after such modifications or otherwise. Please
check that you have the latest issue of the 'Technical Data
Sheet'. All slitting and length tolerances are to British
Standards. Before use the customer is advised to consult
the Health & Safety Data Sheet produced by the company
for this product, which is available on request.
STORAGE
Tapes stored below the minimum recommended tempera -

Tapes stored below the minimum recommended tempera ture will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA Association des Fabricants Européens de Rubans Auto-Adhésifs.

Advance Tapes International Limited, PO Box 122, Abbey Meadows, Leicester, LE4 5RA. Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com