

Technical Data

Issue 09 February 2000

AT8H Hazard Warning Tape

General description

A heavy duty plasticised PVC film coated with a white aggressive pressure sensitive adhesive

- Flexible.
- Water resistant.
- Good abrasion resistance.
- UV resistant.
- Non-corrosive adhesive.
- High level of adhesion.
- Can be walked on immediately after application.
- Suitable for machine and hand application.

Specifications

Certification* to the following standards may be available on request.
BS3887 : 1991 all colours

Technical Details

Typical values

Tape Thickness	0.14mm
Breaking Load	26 N/cm
Elongation at Break	150%
Adhesion	
Steel	3.5 N/cm
Self	2.5 N/cm
Water Extract	
pH	6.0 to 8.0
Conductivity	Max.2.5 mS/m
Service Temperature	0°C to +60°C
Application Temp	+5°C to +40°C

*Standard charge for certificate: £25.00.



NOTE

Except where indicated otherwise, the above figures are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

 **ADVANCE**
adhesive tapes



BS EN ISO 9002
Q05206



INVESTOR IN PEOPLE

AFERA

Association des Fabricants Européens de
Rubans Auto-Adhésifs.

Advance Tapes International Limited, PO Box 122,
Abbey Meadows, Leicester, LE4 5RA.
Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com