

DigiMask™ Clear features a specially-formulated 3.5 mil polypropylene film, which stays rigid during hot weather graphics applications to prevent stretching and misalignment of graphic panels. As a surface protection premask for large format digital prints the exceptional clarity of the film allows the end user inspect the print prior to acceptance of the job.

PHYSICAL SPECIFICATIONS

Adhesive	Solventless
Color	Clear Blue Tint
Caliper <i>facestock</i>	90 microns (3.2 mils)
Caliper <i>facestock + adhesive</i>	115 microns (4.5 mils)
Adhesion to Steel*	4.3 -7.7 N/100mm (4 - 7oz.)
Tensile	297-332 N/100mm (17 - 19 lb./in)
Elongation	650%
Shelf Life**	1 year

APPLICATIONS

- Aids Application of Vehicle Wraps
- Surface Protection Film for Wide Format Digital Prints.

PRINTER PROFILES

Printer profiles are available on rtape.com.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

FEATURES

- Specially-designed clear surface protection film aids application of full or partial vehicle wraps.
- In hot weather applications, the rigid polypropylene film resists stretching to prevent misalignment of graphic panels during application.
- Exceptional clarity allows quality inspections as well as aids registration of printed graphics panels during installation.
- Unwinds easily for more user-friendly lamination.
- Low tack adhesive removes easily without pulling overlaminates from the graphics or applied graphics from the substrate.
- Factory cut rolls with perfectly cut edges.



RTape Corp.
 6 Ingersoll Road
 South Plainfield, NJ
 07080
 T 1-800-440-1250
www.rtape.com

RESPONSIVE
 RELIABLE
 RESOURCEFUL