

## FICHA TÉCNICA

REFERENCIA: POLIPROPILENO PARA IMPRESIÓN



### TECHNICAL DATA SHEET OF 50micron BOPP PACKING TAPE-23562#

DESCRIPTION (SIZE)	ADHESIVE (BACKING)	COLOR	TOTAL THICKNESS (mm)	TACK (#)	PEEL (kg/in)	HOLDING POWER (min.)	TENSILE STRENGTH (MD,kg/in)	ELONGATION AT BREAK (MD,%)
Bopp packing tape	Acrylic emulsion (Bopp film 25 um)	Clear/White	0.050±0.003	≥26	≥0.80	≥1440	≥9.00	≥150
REMARK	Application temp.: -10 <sup>0</sup> C~65 <sup>0</sup> C							

#### TEST METHOD:

TOTAL THICKNESS: ASTM D-3652

TACK1: PSTC-6 TACK2: J.DOW.METHODS

PEEL: 180° ADEHESION TO STEEL, PSTC-1 (ASTM D-3330)

HOLDING POWER: SHEAR TO STEEL, 1"\*1"\*1KG, 178<sup>0</sup>, PSTC-7 (ASTM D-3654)

TENSILE & ELONGATION : PSTC-31 (ASTM D-3759)

SEALING CARTON TEST: KLL METHOD

TESTING WERE CARRIED OUT IN 23±2<sup>0</sup>C AND 65±5%RH.

**Suministros Jesvy S.L.U** [www.jesvy.com](http://www.jesvy.com)

C./ Sequia de Benager, 22 Pol. Ind. Alquería de Moret, 46210 Picanya  
Tel 96 392 35 55, Fax 96 391 32 01, E-mail comercial@jesvy.com