



DECORATIVE FILM

INT 540 BLACKOUT PATTERN

INTERNAL INSTALLATION



CURVES AND CIRCLES

DESCRIPTION

Decorative films make it possible to personalize a window, a glass partition or cabinet while maintaining privacy. These films soften the light without reducing the luminosity and bring a touch of originality to the decoration of your projects.



Durability : 12 to 15 years for vertical application in Central Europe.



Use : for all types of glazing.



Maintenance : after 30 days with a usual cleaning solution (non-abrasive, without ammonia...). Cleaning products that could scratch are to be avoided.



Storage : 2 years from delivery. This film must be stored away from excessive humidity and away from direct sunlight, at a temperature below 38°C.

In order to satisfy a high level of requirement, we recommend that you do not mix films from different productions

INFORMATIONS

MATERIAL :PET
ADHESIVE :Acrylic polymer 13 gr/m²
LINER :PET siliconé 23 microns
THICKNESS :23 microns
COLORE :Colorless
APPLICATION FACE :Interior
APPLICATION T° :min, + 5°C
STANDARDS:EUROCLASSE
FIRE RANTING : B-s1,d0
GUARANTEE:10 years indoor*

* For glazing not exposed to the sun

DIMENSIONS

By roll :



1,52 x

5 m
10 m
30 m

Notice
of application



Video
posing



Method of application

The surface to be bonded must be free of dust, grease or any other contaminants. Certain materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility of placing on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify the colors and manufacturing processes without notice. We recommend that our users, before applying our films, ensure that they are exactly suitable for the intended use and that they comply with the standards in force.