

CDA180

HIGH GRADE

CLOTH DUCT TAPE

PRODUCT DESCRIPTION:

Mesh 50 Black / Grey / Brown cloth backing, combined with a high performance synthetic rubber-resin adhesive,

FEATURES:

- cloth backing provides excellent reflection of both heat and light.
- High quality adhesive with super strong adhesion and holding power offers reliable a
- Low moisture vapor transmission rate makes **CDA180** an excellent vapor barrier.
- Service Temperature range from -20° to +80°C (-4° to +176°F).

TYPICAL PHYSICAL PROPERTIES:

PROPERTIES	METRIC	ENGLISH	TEST METHOD
Cloth Backing	Mesh	50	
Adhesive Thickness	155 Micron	6.1 Mil	PSTC-133
Total Thickness	280 Micron	11.0 Mil	PSTC-133
Peel Adhesion	25 N/25mm	90 Oz./In.	PSTC-101
Rolling Tack (11mm ball)	≤ 2.5 cm	≤ 1.0 In.	PSTC-106
Service Temperature Ranger	-20 ~ +80 °C	-4 ~ +176 °F	-----

PRODUCT FORM & SIZE AVAILABLE:

Cut Roll: 25/ 48 / 50mm (2") / 60 / 63mm (2.5") / 72 / 75mm (3") / 96mm / 100mm (4").

Log Roll: 1060mm x 50m

Jumbo Roll: 1060mm x 1000m

STORAGE & SHELF LIFE: One year when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

SURFACE PREPARATION: It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

PRODUCT USE: It is essential that the user evaluate the product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on product between +10 ~ +40°C (+50 ~ +105 °F).

LIMITED WARRANTY & LIMITED REMEDY: Your exclusive remedy & obligation shall be, at our tape's option, to replace or repair the product or refund the purchase price of the product.

