



30.900N | Total Mirror

This polyester printable mirror film is suitable for indoor and short-term outdoor use. With its two-way mirror effect, it seamlessly adapts to flat and subtly curved surfaces, providing design flexibility. This film is ideal for decorative applications in diverse settings like fashion stores, hospitals, and petrol stations.

FACE FILM

PET, silver mirror

Thickness (µm)	190
----------------	-----

ADHESIVE

Clear solvent-based acrylic, permanent

Thickness (µm)	20
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	11
24 hours (180°) N/25mm	13

RELEASE LINER

Clear PET liner

Thickness (µm)	20
----------------	----

PROTECTION FILM

Thickness (µm)	20
----------------	----

PRODUCT APPLICATION

Dimensional stability (.mm)	<1
Application temperature (°C)	10 to 25
Service temperature (°C)	-30 to 60

DURABILITY

Outdoor durability (years)	1	Vertical exposure, Mid-EU climate
Shelf life (months)	18	

ROLL SIZES

1220mm x 25m
1220mm x 50m

PRINTING METHOD

Latex
UV Angular alignment of printheads only

Fourbases BV warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. Fourbases BV only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.

