

One Way Vision – QSV18P-14

Specification	Description	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	150 ± 10um
	Color Code	White
	Back	Black coating
	Shrinkage	≅ 0.8%
	Surface Tension	≅ 30dn/cm
	Opacity	>99%
	Holes No.	Average 130/sq in
	Hole Diameter	1.6mm
	Distance Between Holes	2.4mm
	Hole Space	41%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Thickness	30 ± 2um
	Adhesion Temperature	15°C ~ 40°C
	180° Peeling Force	≅ 5N/25mm (GB2792-81 China National Standard)
	Initial Adhesion- Ball Tack	≅ 5# Steel Ball (GB4852-84 China National Standard)
	Holding Power	≅ 800min (GB4854-84 China National Standard)
	Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23-25 C and RH of 50-60%
Liner	Type	Kraft Paper
	Color	white
	Weight	140g ± 5g/m ²
	Release Force	0.4~1N/4mm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Outdoor digital printing and silk screen printing one way vision media for signage display, vehicle graphics , subway and glass walls of building	

Compatibility of machines and ink	<p>Media is suitable for all solvent and eco solvent digital printers with heating system including Infiniti, Phaeton, Mimaki , Roland, Vutek and HP Scitex.</p> <p>Inks should be the original ink from the printer manufacturers. The best printing temperature is 40-43°C.</p>
-----------------------------------	---