

YUPO EUROPE GmbH

Schiessstrasse 47 D-40549 Düsseldorf +49 (0) 211 520 54 30 www.yupo.eu

Data Sheet:

YupoTako Flex

XAD 1095

About the product:

- YUPOTako has a suction layer on the backside to stick to flat surfaces.
- YUPOTako Flex XAD 1095 is designed for UV offset, UV-silkscreen and UV digital printing. It has a different touch compared to existing grades and provides a more flexible feeling when sticking and peeling off.
- For additional information, please refer to YUPOTako leaflet.

Printing Method:

UV-Offset, UV-Siebdruck, UV-Digital

Physical Properties (measured values):

Thickness		micron	197
Basis Weight		g/m²	160,0
Density		g/cm³	0,80
Brightness		%	95
Opacity		%	90,6
Gloss (Top/Bottom)		%	21
Tensile Strength	MD	kN/m	-
	CD	kN/m	-
Elongation	MD	%	-
	CD	%	-
Tear strength	MD	mN	-
	CD	mN	-
Clark stiffness	MD	s-value	-
	CD	s-value	-
Surface resistance		omega	-

This document is provided for informational purposes only and is not intended to be a specific agreeement. YUPO EUROPE reserves the right to make changes to the values shown as required to improve product performance.

Issued: June 2023 YUPO Europe Uncontrolled Document