

NF04-B Magnetic sheeting (Ba) -SPECIFICATION SHEET-

Date: 2025-6-5

Size

1. NF04-B 20m×1270×0.4mm/MUV/2.0mm Pole pitch/Matte white PVC
2. NF04-B 10m×1020×0.75mm/MUV/2.0mm Pole pitch/Matte white PVC

Dimensions: & Tolerance:

Item	Length(m)		Width(mm)		Thickness (mm)		PVC Thickness (mm)
Size	20	10	1270	1020	0.4	0.75	0.1~0.13
Tolerance	0/+0.6	0/+0.6	-1/+5	-1/+5	±0.04	±0.05	

Pull Strength:

Code	Thickness (mm)	Pole pitch (mm)	Pull (g/cm ²)
NF04-B20M	0.40	2.0	≥17
NF04-B10M	0.75	2.0	≥38

Physical Data:

Total thickness (mm)	0.50±0.05	0.85±0.06
Reference Weight (g/m ²)	1540±154	2690±270
Hardness (Shore D)	45±5	45±5
Flexibility (Φ 6mm)	Without cracking	Without cracking
Opacity	100%	100%
Water resistance	High	High

For reference, it works within the range of - 20 °C to +70 °C of the ambient temperature, and the customer needs to test the actual application environment.

Storage Condition: 25°C and 50% humidity conditions

Shelf life: 12 months under original packaging condition

The magnetic force is permanent and will not degrade in normal temperature without strong magnetic interference.

