## PRODUCT DATA SHEET

# Avery Dennison® MPI 3800/3820 Series

Issued: 08/2025

#### Introduction

Conversion

Avery Dennison Multi Purpose Inkjet 3800 series films are gloss white and matt white self-adhesive monomeric calendered vinyls, offering a choice between permanent clear and permanent grey adhesives.

MPI 3800 series films are multi-purpose vinyls, suitable for a variety of wide-format inkjet printers using hard

solvent, eco/mild solvent, UV-curing or latex inks.



#### **Face Film**

MPI 3800/3803 90 µm white Gloss PVC film

MPI 3820/3823 90 µm white Matt PVC film



#### **Adhesive**

MPI 3800/3820 Permanent, clear acrylic based

MPI 3803/3823 Permanent, grey acrylic based



#### Backing

PE Coated Kraft paper, 140 g/m<sup>2</sup>





#### **Durability**

6 months



# **Shelf Life**

1 year

#### Recommendations

- Interior & exterior signs
- Short term in- and outdoor advertising
- » Posters, panels and signs at exhibitions
- Point of sale promotions
- Applications to flat or regular surfaces where additional opacity may be required

### **Features**

- Excellent printability and handling on selected printers >>
- Easy cutting and application on a wide variety of substrates
- Excellent price/performance ratio for promotional graphics
- Excellent opacity by using grey adhesive system for overposting needs



#### **Physical Characteristics**

	Test method <sup>1</sup>	Results
Product		
Caliper, facefilm (micron)	ISO 534	90
Caliper, facefilm + adhesive (micron)	ISO 534	120
Dimensional stability (mm max.)	FINAT FTM 14	1.2
Shelf life (years)	Stored at 22° C/50-55 % RH	1
Durability <sup>2</sup>	Vertical exposure	6 months
Flammability	EN 13501-1	B-s1, d0
Adhesive		
Adhesion, initial (N/m)	FINAT FTM-1, stainless steel	MPI 3800/MPI 3820: 480
		MPI 3803/MPI 3823: 400
Adhesion, ultimate (N/m)	FINAT FTM-1, stainless steel	MPI 3800/MPI 3820: 640
, tarresieri, atamate (rum)	Thurst Time 1, standed steel	
		MPI 3803/MPI 3823: 600
Temperature range		
Application temperature (Minimum: °C)	)	+10°C
Service temperature (°C to +°C)		-20°C to +80°C

- - 4 --- - 41- - -11

D = = . . I4 =

#### **Important**

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

- 1) Test methods: More information about our test methods can be found on our website.
- 2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased..

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://lems.europe.averydennison.com.

Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

© 2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

