BLACK BACK BACKDROPS FABRIC

-100% warp-knitted polyester fabric with white surface and black resin coating backside, makes it fully opacity for backdrops applications
-Slight stretch feature makes it perfect as frame and Pop-up materials
-Compatible with Dye-sub direct, Dye-sub transfer, also workable with UV & Latex inks

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2,ASTM D 751	250 g/sq.m	7.3 oz/sq.yd
Base Fabric	DIN 60001,ASTM D7641	100%Polyester	100%Polyester
Yarn Dtex	DIN EN ISO 2060,ASTM D 1907	61x83 dtex	55x75 denier
Weave Method	N/A	Warp-knitted 2bar	
Shrinkage	190℃，1min	≤3%	
Elasticity	Length*Width=200*50mm，Speed=100mm/min，Tension=20N	Warp：2-4% Weft：1-3%	
Flame Resistance	EN13501, DIN 4102-1-B1， NFPA 701	EN13501, DIN 4102-1-B1， NFPA 701	
Recommend Fixation Temperature	N/A	170℃-180℃，7min	
Calender Fixation Temperature	N/A	190℃，1min	
Yellowing temperature	SUPRKC REX-C400, 30s	≥210℃	
Width	DIN EN ISO 3759,ASTM D751-2006	Max 505cm	199“
Standard Length	DIN EN ISO 3759,ASTM D751-2006	50m	55yd
Compatiable Inks	N/A	Dye-sub Transfer,Dye-sub Direct, UV,Latex	
Application	N/A	Backdrops,Pop-up, Frame, Exhibition,Display systems	

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		□	□
Screen Printing	**Dye Transfer**	**Dye Direct**	
	□	□	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

C/ Sèquia de Benàger, 22
Pol. Ind. Alqueria de Moret
46210 Picanya VALÈNCIA
96 392 35 55
www.jesvy.com
comercial@jesvy.com