



ANTI REFLECTION FILM

ARF 100

EXTERNAL APPLICATION



The ARF 100 film is an anti-reflection film that reduces and even suppresses unsightly reflections to have clear and transparent windows.

INFORMATION

MATERIAL:	PET
ADHESIVE:	Acrylic polymer
THICKNESS:	100 microns
UVA TRANSMISSION:	1%
COLOR:	Transparent
APPLICATION FACE:	External
THERMAL RESISTANCE:	From -20°C to 80°C
APPLICATION T°:	min. + 5°C
FIRE RATING:	B-S1, D0
STANDARDS:	EUROCLASSES
DURABILITY:	10 years

Length by linear meter

Width: 1.52 m

Maximum length: 30 m



* For glazing not exposed to the sun

Application's notice



Application's video



Durability: 10 years for vertical application in central Europe.



Use: Reflectiv window films are designed for use on any type of clear normal glass.



Maintenance after 30 days: with usual cleaning solutions (non-abrasive, without ammonia...). Cleaning products that may scratch the film should be avoided.



Storage: 2 years from delivery. This film should be kept away from excessive humidity and sun rays, at temperatures below 38°C.

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice.

Application Method

The glass surface to be glued on has to be free from dust, grease or other contaminants. Some specific materials such as polycarbonate can cause air bubble problems. Therefore, a compatibility test is recommended. For more precision we recommend to refer back to the application table.

Production and standards

In order to constantly improve our production we may change product colour and manufacturing process without prior notice. Before applying our products we recommend that our users ensure that the film is suitable for the intended use and comply with current standards.